8) CHECK LED STATUS


Turn your machine ON and check the LEDs status

Full LED status information on www.pinsound.org/support

Motion Control



MasterEffect



IF NEEDED: UPDATE THE MASTER EFFECT



- Update the firmware of your Master Effect board www.pinsound.org/support
- Download and copy the PSPACK Original file at the root of the flash drive

www.pinsound.org/machine

(10) ENJOY!

Have fun with your new shaker!

(2) NEED HELP?

Installation video Firmware update Guide Q&A



PinSound Motion Control MasterEffect



Standalone shaker kit for Data-East

(KIT CONTENT











Master Effect

Shaker motor

Plastic cover Control wire

Shaker power Power splitter









Motion Control

DE MFX 5V

MFX DATA





7/32" 5.5 mm drill bit


(F) TOOLS

1/4" nut driver Phillips screwdriver


Installation manual

Drill template

1) LOCATE THE CORRECT SPOT 2) CLEAN THE AREA




In order for the backbox to close, the 2 boards have to be placed behind the metal hook




The Motion Control & Master Effect boards will be installed on the right inner side of the backbox

(3) MOUNT ADHESIVE FEET



(4)STICK THE BOARDS & CONNECT


- > Connect EXT1 from Master Effect to Motion Control
- > Connect CN4 splitter to SHAKER POWER INPUT
- > Connect SHAKER MOTOR wire and lay it down to the cabinet
- > Connect CN2 splitter to 5V DC POWER
- > Connect MFX DATA from SOUND to DATA 2



(5) PREPARE THE DRILL AND THE TEMPLATE









Cut off the Data-East drill template

(6) PREPARE THE SHAKER FITTING




Place the template as indicated and drill the 4 holes




Hammer down the 4 T-Nuts under the cabinet


(7)INSTALL THE SHAKER



Place the shaker and secure it with the 4 screws



Place the shaker cover and secure it with the 4 screws



Connect shaker power wire